

WaveMon RF-40

Personal EMF Monitor



OVEREXPOSURE WARNING
Audible, visual and vibratory alarm



EMF EXPOSIMETER
Datalogger, instant & average values



ICNIRP, 2013/35/EU, FCC, SC6
Weighted response



ISOTROPIC RMS
Electric Field Sensor



Harness, Belt and Arm Holder

E-Field Isotropic Sensors with RMS Response

Datalogger
Instant and Average Values

Exposure Level as a % of the Standard/limit

Rechargeable and Replaceable Batteries for 200 h Autonomy

ON/OFF Status Button

GPS and Altimeter (Optional)

High Intensity Audible and Vibratory Warnings

USB and Tripod Connectors



WaveMon Applications.



Worker's safety



Telecommunications



Railway



Medical



Labs



Aeronautical



Industry



Defense

Technical Specifications



Optional accredited calibration

Sensor type	Isotropic, RMS diode technology
Response	Shaped to specific standards
Dynamic range	1 - 300 %
Linearity	±0.5 dB (2% - 200%)
Isotropic deviation	±1 dB @ 1GHz
Interface	1 button on/off, status and low battery LED
Indicators	6 LEDs + Audio + Vibration
Alarm threshold	2 limits adjustable by user
Connectivity	Waterproof USB (for downloading data and recharging)
Falling detection	Yes
Autonomy	>1 month (at 8 h/day, 5 days/week)
Data logger	>1 000 000 events
Positioning	GPS and Altimeter (Optional)
Logging Interval	1 second to 60 minutes (adjustable by user)
Averaging Interval	1 second to 60 minutes (adjustable by user)
Battery Type	2 x AA NiMH battery rechargeable by USB
Protection	IP 54
Temperature range	-20 / +50 °C (-4 / +122 °F)
Size	174 x 42.5 x 33 mm (6.8 x 1.7 x 1.3 ")
Weight	190 g (6.7 oz.)

	Response shaped to	Frequency range	Frequency response
WaveMon RF-40 ICN	ICNIRP	1 MHz - 40 GHz	1 MHz - 6 GHz: ±3.5 dB 6 GHz - 35 GHz: ±6 dB 40 GHz: +10 dB
WaveMon RF-40 FCC	FCC	1 MHz - 40 GHz	1 MHz - 6 GHz: ±3.5 dB 6 GHz - 35 GHz: ±6 dB 40 GHz: +10 dB
WaveMon RF-40 EUD	EU Directive 2013/35	1 MHz - 40 GHz	1 MHz - 6 GHz: ±3.5 dB 6 GHz - 35 GHz: ±6 dB 40 GHz: +10 dB
WaveMon RF-40 SC6	Safety Code 6	10 MHz - 40 GHz	10 MHz - 6 GHz: ±3.5 dB 6 GHz - 35 GHz: ±6 dB 40 GHz: +11 dB
WaveMon RF-40 NATO	NATO standards	1 MHz - 40 GHz	1 MHz - 6 GHz: ±3.5 dB 6 GHz - 35 GHz: -4/+8 dB 40 GHz: +13 dB

Product specifications and descriptions in this document subject to change without notice



WAVECONTROL
Safety. Quality. Service



TES America
www.tesamerica.com
info@tesamerica.com
TES America México
015536834284
TES America Colombia
PBX +571-3653949